
Panoramica

Informazioni sul prodotto



15EDGVC-THR-2.5 Reel package-10030000843

Pluggable terminal blocks,Rated current:5A.Rated voltage（Ⅲ/2）:250V,pitch:2.5mm,Color:black,Contact surface :Tin

Vantaggi del prodotto

☑ Suitable for SMT welding process
☑ The plug direction is perpendicular to PCB，Can meet the needs of different connectors

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	150V
Rated current (B)	4A

Electrical parameters IEC

Rated voltage	250V
Rated current	5A
Rated voltage(Ⅲ/2)	250V
Rated surge voltage(Ⅲ/2)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~130℃

Accessori

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/

Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10030000843
Unità di imballaggio	220
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	0.78