
## Panoramica

### Informazioni sul prodotto



# 15EDGRM-THR-3.5-10030003349

Pluggable terminal blocks,Rated current:8A.Rated voltage（Ⅱ/2）:250V,pitch:3.5mm,Color:black,Contact surface :Tin

### Vantaggi del prodotto

☑ Suitable for SMT welding process
☑ The plug direction is parallel to the PCB，Can meet the needs of different connectors

### Certificazione del prodotto

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Processing notes

| | |
|---|---|
| Process | Reflow soldering/wave soldering/manual soldering |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 8A |

### Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 250V |
| Rated current | 8A |
| Rated voltage(Ⅱ/2) | 250V |
| Rated surge voltage(Ⅱ/2) | 2.5KV |

## Item properties

| | |
|---|---|
| Connection direction | 0° |
| Type of installation | PCB welding |
| Pin arrangement | Single row in a straight line |
| Pitch | 3.5mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

## Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact zone metal surface | tin-plated |
| Insulation Materials | High temperature resistant materials |
| Insulating material group | IIIa |
| Flammability rating | UL94V-0 |

## Mechanical tests

| | |
|---|---|
| Test Specification | IEC60947/UL1059 |

## Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~130℃ |

# Accessori

## Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

## Accessories

| | |
|---|---|
| Coding strip | / |
| Bridge | / |
| Marking strip | / |
| Others | / |

## Dati aziendali

| | |
|---|---|
| numero d'ordine | 10030003349 |
| Unità di imballaggio | / |
| Quantità di ordine minimo | 30 |
| Peso dei prodotti (senza imballaggio) | 1.208 |