
## Aperçu

### informations sur le produit



# DS2.5-3L-PE-11040000129

Three-layer terminal blocks, wiring method: direct insertion connection, rated voltage: 500 V, connection quantity: 6, digit: 1, wiring capacity: 0.2 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, color: yellow-green, installation method: NS35/7.5, NS35/15

### Les avantages des produits

☑Multi-level terminal block.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Unique plug-in bridge, high circuit connection efficiency.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

### Les certificates des produits

## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

### Wiring data

| | |
|---|---|
| Strip length | 10~12mm |
| Conductor cross section solid AWG | 26~12 |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

### IEC Electrical parameters

| | |
|---|---|
| Rated surge voltage | 6KV |

### Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

### Dimension

| | |
|---|---|
| End plate width | 2.2mm |
| width | 5.2mm |

### Overview

| | |
|---|---|
| Connection type | In line connection |
| Number of rows | 3 |
| number of connections | 6 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

## Accessoires

### Marker

| | |
|---|---|
| Top marker | / |
| Side marker | ZSF5 |
| Marker support | DMTH5-2 / DMTH5-3 |

### Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) mm | 0.6x3.5 |
| Bridge | DFBXX-5.2 |
| End cover | D-DS2.5-3L |

### Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

## Caractéristiques commerciales

| | |
|---|---|
| Numéro de la commande | 11040000129 |
| Unité d'emballage | 50 |
| Quantité minimale de commande | 50 |
| Le poid de produit (sans emballage) | 24.63 |