
Aperçu

informations sur le produit



2EDGVHM-5.0-10030004860

Pluggable terminal blocks,Rated current:10A.Rated voltage（III/2）:320V,pitch:5.0mm,Color:green,Contact surface :Tin

Les avantages des produits

☑ Universal installation method to ensure a high degree of flexibility in device design
☑ Multi-layer wire connection can achieve higher contact density

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	10A

Rated voltage(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	5mm
Number of potentials	8
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessoires

Tool

Screwdriver	/

Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	2EDG-PWP

Caractéristiques commerciales

Numéro de la commande	10030004860
Unité d'emballage	165
Quantité minimale de commande	30
Le poid de produit (sans emballage)	13.05