
종람

제품 장점



## WS4-PE-100A(H)-11030000291

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 28 - 12, Width: 6 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

제품 장점

☑spring-cage connection technology, good anti-vibration performance；
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire；
☑Grounding structure, protection circuit；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

제품 인증

기술 데이터

제품 도면

3D

Wiring data

| | |
|---|---|
| Strip length | 10~12mm |
| Conductor cross section solid | 0.2~4mm² |
| Conductor cross section flexible | 0.2~4mm² |
| Conductor cross section solid AWG | 28~12 |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

### IEC Electrical parameters

| | |
|---|---|
| Rated surge voltage | 8KV |

### Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

### Dimension

| | |
|---|---|
| NS 35/7,5 Height | 36.45mm |
| End plate width | 2.5mm |
| NS 35/15 Height | 43.95mm |
| length | 60.4mm |
| width | 6mm |
| Height | 34.45mm |

### Overview

| | |
|---|---|
| Connection type | Pull back spring connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | Yes |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

## 악세사리

### Marker

| | |
|---|---|
| Top marker | ZB6 / WB5 |
| Side marker | DEK6 |
| Marker support | DTH5-25×5 / DTH5-25×12 |

| | |
|---|---|
| Warning cover | EEA4 |

## Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P) | / |
| Alternate jumper (2P) | / |
| Staggered jumper (2P) | / |
| End cover | D-WS4 |

## Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 11030000291 |
| 포장 단위 | 50 |
| MOQ | 50 |
| 제품 무게 (포장 제외) | 13.42 |