종람

제품 장점



## MDR cable-DX220-3S-500-00A(H)-23040000070

MDR cable,connector1:MDR connector（1×20 Core,180° output）,connector2:IDC/MIL female connector（1×20 Core,180° output）

제품 장점

☑The cable is soft and has good bending resistance
☑Prefabricated connector, beautiful appearance
☑ Provide single-ended and double-ended cables
☑ Suitable for servo position control mode
☑ Save wiring time, and can achieve fast wiring with the company's interface module

제품 인증

기술 데이터

제품 도면

3D

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -20 °C ... 80 °C |
| Ambient temperature (storage / transport) | -20 °C ... 80 °C |

Standards/Regulations

| | |
|---|---|
| Flame retardant | ULVW-1 |
| Oil resistance | Oil resistant |
| Gasoline resistance | ≤246Ω/KM |
| Connection meets standards | UL758 |

Technical data

| | |
|---|---|
| Maximum allowable working voltage | 30VDC |
| Maximum current carrying capacity of each path | 0.7A |
| cable length | 0.5米 |
| Cable outer diameter | 6.1mm |
| Single strand, cross-sectional area | 0.08mm² |
| Single strand, cross section (AWG) | 28 |

Connection data 1

| | |
|---|---|
| Connection name | On-site side |
| Connection method | IDC/MIL female connector |
| Connection volume | 1 |
| Number of digits | 20 |
| spacing | 1.27mm |
| Exit angle | 180° |

Connection data 2

| | |
|---|---|
| Connection name | On-site side |
| Connection method | IDC/MIL female connector |
| Connection volume | 1 |
| Number of digits | 20 |
| Exit angle | 180° |
| spacing | 2.54mm |

Overview

| | |
|---|---|
| Single wire, number of twisted wires | 20 |
| Single stranded wire, material | Tinned copper |
| shield | Yes |
| Outer sheath, material | PVC |

| | |
|---|---|
| Outer sheath,color | black |

## 악세사리

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 23040000070 |
| 포장 단위 | 1 |
| MOQ | 10 |
| 제품 무게 (포장 제외) | 50 |