
Aperçu

informations sur le produit



DSKK2.5-PE-11040000099

Double-layer terminal blocks, wiring method: direct insertion connection, rated voltage: 500 V, connection quantity: 4, digit: 1, wiring capacity: 0.2 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, color: yellow-green, installation method: NS35/7.5, NS35/15

Les avantages des produits

☑Double-level terminal block.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑Unique plug-in bridge, high circuit connection efficiency.
☑Optional marker to avoid wire mis-inserting.
☑Equipped with test holes for easy testing of the circuit.

Les certificates des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	48.75mm
End plate width	2.2mm
NS 35/15 Height	56.25mm
length	68.2mm
width	5.2mm

Overview

Connection type	In line connection
Number of rows	2
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessoires

Marker

Top marker	/
Side marker	ZSF5
Marker support	DMTH5-2 / DMTH5-3

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5

Bridge	DFBXX-5.2
End cover	D-DSKK2.5

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Caractéristiques commerciales

Numéro de la commande	11040000099
Unité d'emballage	50
Quantité minimale de commande	50
Le poid de produit (sans emballage)	13.017