概要

製品情報



# D32B-TE-2g-M50-21010000541

32BHoods,double levers,top entry,M50 Thread hole

製品の特長

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock;
☑Various installation methods and outlet directions to meet on-site wiring requirements;
☑Snap-in combination structure, dustproof, waterproof, easy operation;

製品認証

技術データ

製品チャート

3Dモデル

Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | B |
| Type | Top housing |
| Specification | High structure |

Versions

| | |
|---|---|
| Dimension | 32B |
| locking Category | Single lock |
| Wiring method | Top entry |
| Thread specification | 1x M50 |

Material characteristics

| | |
|---|---|
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

## アクセサリ

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 21010000541 |
| パッキングユニット | 100 |
| 最小注文数量 | 1 |
| １個あたりの重量（梱包を含めない） | 432 |