
종람

제품 장점



## WS35-11030000266

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 1000 V, Rated current: 125 A, Number of connectors: 2, Number of potentials: 1, Cross section: 2.5 mm² - 35 mm², AWG: 14 - 2, Width: 16 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

제품 장점

☑spring-cage connection technology, good anti-vibration performance；
☑Use an ordinary flat-blade screwdriver, you can easily wire and take the wire；
☑Unique plug-in bridge, high circuit connection efficiency；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

제품 인증

CE

기술 데이터

제품 도면

3D

Wiring data

| | |
|---|---|
| Strip length | 25mm |
| Conductor cross section solid | 0.2~35mm² |
| Conductor cross section flexible | 0.2~35mm² |
| Conductor cross section solid AWG | 14~2 |

Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |
| Relative humidity (storage/transport) | 25%~75% |

## UL Electrical parameters

| | |
|---|---|
| Rated current | 115A |

## IEC Electrical parameters

| | |
|---|---|
| Rated voltage (III / 3) | 1000V |
| Rated current (III / 3) | 125A |
| Rated surge voltage | 8KV |

## Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

## Dimension

| | |
|---|---|
| NS 35/7,5 Height | 59.2mm |
| NS 35/15 Height | 66.7mm |
| length | 99.9mm |
| width | 16mm |
| Height | 58.4mm |

## Overview

| | |
|---|---|
| Connection type | Pull back spring connection |
| Number of rows | 1 |
| number of connections | 2 |
| Open-end side panels | no |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |

악세사리

## Marker

| | |
|---|---|
| Top marker | ZT12 |
| Side marker | / |
| Marker support | DTH5-25×5 / DTH5-25×12 |
| Warning cover | / |

Accessories

| | |
|---|---|
| Slotted screwdriver size (Blade thickness x Width) | 1×5.5 |
| Adjacent jumper (2P) | / |
| Alternate jumper (2P) | / |
| Staggered jumper (2P) | / |
| End cover | / |

Installation

| | |
|---|---|
| End clamp | E-WS N / E-PC-1100A |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail | NS35/7.5-1000-00A(H) |

Marking & Installation

| | |
|---|---|
| Marking strip | ZB10 |
| Marker cards | DBE-1 |

Accessories

| | |
|---|---|
| End clamp | E-WS |
| DIN rail | NS35/7.5-1000-00A(H) |

비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 11030000266 |
| 포장 단위 | 20 |
| MOQ | 20 |

| | |
|---|---|
| 제품 무게 (포장 제외) | 78.61 |