概要

## 製品情報



# D2MK-002-M(16-35mm²)-21020000259

Heavy-duty insert,Number of contacts:2,Dimension:2 module Spaces,Rated voltage :1000V,Rated current:100A,Male insert,axial Screw connector

## 製品の特長

☑Axial Screw connection technology, applicable to a wide range of wire specifications;
☑Less materials, easy to manage;
☑Modular products, easy to assemble and maintain 。

## 製品認証

CE

技術データ

## 製品チャート

## 3Dモデル

## Marking

| | |
|---|---|
| classification | Insert |
| Series | DM |

## Versions

| | |
|---|---|
| Connection method | Axial screw connection |
| Female/Male | Male |
| Dimension | 2 module |
| Number of positions | 2 |
| PE Contacts | No |

## Material characteristics

| | |
|---|---|
| Material（insert） | Polycarbonate（PC） |
| Materia（Contact） | Copper alloy |
| Surface（Contact） | Silver plated |
| Flammability rating | V-0 |
| color | Grey/White（RAL 7032） |
| RoHS | Comply with RoHS exemptions |

Electrical parameters

| | |
|---|---|
| Rated current | 100A |
| | 1000V |
| Rated pulse voltage | 8KV |
| Pollution level | 3 |
| On the basis of UL /CSARated current | 600V |
| Insulation resistance | ≥10000MΩ |
| Contact resistance | ≤0.3mΩ |
| Temperature range | -40℃~+125℃ |
| working life-mating cycles | ≥500 time |
| Strip length | 13mm |
| Rated torque | 8N.m(25/35mm²) 9N.m(50mm²) 10N.m(70mm²) |
| Conductor cross sections（mm²） | 16-35mm² |
| Conductor cross sections(AWG) | 6-2AWG |

Standards

| | |
|---|---|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |

アクセサリ

Accessories

| | |
|---|---|
| SW 4 internal hexagonal wrench | / |

ビジネスデータ

| | |
|---|---|
| 注文番号 | 21020000259 |
| パッキングユニット | 100 |
| 最小注文数量 | 5 |
| 1個あたりの重量（梱包を含めない） | 80 |