## Überblick

### Informationen zum Produkt



# DPV2.5-92119900085

Upper and under Bridges, suitable for upper and under Bridges between two layers

### Produktvorteile

☑Upper and under Bridges;
☑suitable for upper and under Bridges between two layers;

### Zertifizierung von Produkten

## Technische Daten

### Produktzeichnung

### 3D-Modell

### Overview

| | |
|---|---|
| Number of potentials | 1 |
| Insulation Materials | PA |
| Flame retardant grade, in line with UL 94 | V0 |
| color | Gray |

### Dimension

| | |
|---|---|
| Height | 31.45mm |
| length | 4.9mm |
| width | 4mm |

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 105 °C（depending on derating curve） |

| | |
|---|---|
| Relative humidity (storage/transport) | 25%~75% |

Environmental protection

| | |
|---|---|
| REACh SVHC | Lead 7439-92-1 |
| RoHS | No excessive harmful substances |

## Zubehör

## Die Geschäftsdaten

| | |
|---|---|
| Nummer der Bestellung | 92119900085 |
| Verpackung Einheit | 200 |
| Minimale Bestellmenge | 200 |
| Produktgewicht (ohne Verpackung) | 0.637 |