概要

製品情報



Relay base-DPKF08A-E3-00A(H)-30020000049

DPKFrelay base,used for2PDTrelay,screw connection

製品の特長

☑Plug-in relay socket
☑Safe isolation between coil and contacts
☑12A, 2PDTgrade
☑Arc partition between adjacent columns
☑Anti-touch cover at the top of the screw

製品認証

技術データ

製品チャート

3Dモデル

Environmental data

Ambient temperature (storage / transport)	-40 °C ... +85 °C
Ambient temperature (operation)	-20 °C ... 50 °C

Technical data

Rated voltage UN	300V
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection

Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Dimension

length	69.6mm
width	25mm
Depth including bracket	29.2mm

アクセサリ

ビジネスデータ

注文番号	30020000049
パッキングユニット	20 SKT
最小注文数量	20 SKT
1個あたりの重量（梱包を含めない）	62g