Überblick

Informationen zum Produkt



DS2.5-TG-11040000207

Knife switch breaking terminal, wiring method: direct insertion connection, rated voltage: 400 V, rated current: 20 A, connection quantity: 3, digit: 1, wiring capacity: 0.2 mm² - 4 mm², AWG: 26 - 12, width: 5.2 mm, color: gray, installation method: NS35/7.5, NS35/15

Produktvorteile

☑Disconnect terminal blocks.
☑Push-in connection technology, tool-free operation, more convenient and faster;
☑With orange wire button, one word or cross screwdriver can release wire.
☑The circuit can be disconnected, measured, controlled easily by operate the knife disconnector.
☑Equipped with test holes on both sides of the breaking point, convenient for testing the circuit.
☑Snap-on knife disconnector to prevent accidental disconnection.
☑Universal breaking area to achieve different functions, can insert breaking plug, component plug, fuse plug.

Zertifizierung von Produkten

Technische Daten

Produktzeichnung

3D-Modell

Overview

Connection method	Push in connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Dimension

NS 35/7,5 Height	36.8mm
End plate width	1.5mm
NS 35/15 Height	44.3mm
length	62mm
width	5.2mm

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated voltage (III / 3)	400V
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Zubehör

Marker

Top marker	ZB5 / ZS5
Side marker	ZSF5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width) mm	0.6x3.5

Bridge	DFBXX-5.2
End cover	D-DS2.5-MT
Matching accessories	DS-DI / DS-CO / DS-FU5 / DS-FU5-LD24

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2
DIN rail	NS35/7.5-1000-00A(H)

Die Geschäftsdaten

Nummer der Bestellung	11040000207
Verpackung Einheit	100
Minimale Bestellmenge	100
Produktgewicht (ohne Verpackung)	7.78