Overview

Product information



PASH-M8A-06P-MM-SL7001-20020000199

Field mounted,Shielded,Male,Straight,M8,Coding A,Soldering connector,Cable External cable diameter 4.0~6.0 mm

Product advantages

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Miniature connector,Space saving
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

Product certification

Technical data

Product drawing

3D model

Environmental conditions

Ambient temperature	-40℃...85℃
IP class	IP67

General parameters

Rated current	1.5A
	30V
Number of potentials	6
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Connection method	Soldering
	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Contact carrier material	PA
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104

Dimension

Assembled cable outer diameter	4.0-6.0mm
Assembled conductor cross section	0.14~0.25 mm²
	26~24 AWG

Accessories

Business data

Order number	20020000199
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/