概要

製品情報



Interface module-DT075-00A(H)-30040000073

Power module, power extension, with screw connector, can be installed on DIN35 rail

製品の特長

Power distribution
Screw connection

製品認証

技術データ

製品チャート

3Dモデル

Environmental data

Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations

Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III
Rated overvoltage	0.5kV
Flame retardant grade, in line with UL94	V0

Technical data

Installation location	Arbitrary

Maximum allowable working voltage	30VDC
Maximum allowable current	10A
Signal points	2
Status Display	no

Connection data 1

Connection name	Control system side
Connection method	Screw connection
Connection volume	1
Number of digits	4
spacing	5.08mm

Connection data 2

Connection name	On-site side
Stripping length	6-7mm
Cross section of flexible conductor	1.0 mm² ... 2.5 mm²
Connectable guide cross section AWG	28-12AWG
Connection meets standards	UL1059
Connection method	Screw connection
Connection volume	1
Number of digits	18
screw thread	M3
Hard wire cross section	1.0 mm² ... 2.5 mm²

Dimension

length	65.6mm
width	57mm
Height	42mm

アクセサリ

ビジネスデータ

注文番号	30040000073
パッキングユニット	2
最小注文数量	10
1個あたりの重量（梱包を含めない）	110