
종람

제품 장점



## 5EDGKD-7.62-10020000918

Pluggable terminal blocks,Rated current:41A.Rated voltage （III/2）:1000V,pitch:7.62mm,Color:green,Contact surface :Tin

제품 장점

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying parts can be installed
☑ Universal installation method, suitable for various situations

제품 인증

기술 데이터

제품 도면

3D

Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.2~10mm² |
| Conductor cross section flexible | 0.2~10mm² |
| AWG | 24~8AWG |
| Strip length | 14mm |

Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 600V |
| Rated current (B) | 35A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 1000V |

| | |
|---|---|
| Rated voltage(III/3) | 1000V |
| Rated current | 41A |
| Rated voltage(III/2) | 1000V |
| Rated voltage(II/2) | 1000V |
| Rated surge voltage(III/3) | 8KV |
| Rated surge voltage(III/2) | 8KV |
| Rated surge voltage(II/2) | 6KV |

Item properties

| | |
|---|---|
| Connection direction | 0° |
| Pitch | 7.62mm |
| Number of potentials | 2 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | copper |
| Contact point metal surface | tin-plated |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## 악세사리

### Tool

| | |
|---|---|
| Screwdriver | / |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | 5EDG-PWI |
| Bridge | / |
| Marking strip | / |
| Others | / |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 10020000918 |
| 포장 단위 | 375 |
| MOQ | 30 |
| 제품 무게 (포장 제외) | 10.27 |