
概要

製品情報



DC4-QU-PE-11020000189

Screw type Din-Rail TB， connector method: Screw/plug-in connector，Number of connectors: 4， Number of potentials: 1， Cross section: 0.5 mm² - 4mm²， AWG: 22 - 10， Width: 6.1 mm， Color: green-yellow， Mounting type: NS 35/7.5， NS 35/15

製品の特長

☑Steel screw connection technology, reliable connection；
☑Grounding structure, protection circuit；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Cross & Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm²
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-2.5mm²
Conductor cross section flexible (ferrule without plastic sleeve)	0.5-4mm²
Strip length	8~9mm
Conductor cross section solid	0.5~6mm²
Conductor cross section flexible	0.5~4mm²

Conductor cross section solid AWG	22~10
screw thread	M3
Tightening torque	0.6N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	49.2mm
End plate width	1.5mm
NS 35/15 Height	56.7mm
length	54.4mm
width	6.1mm
Height	47.7mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	/
Side marker	ZB6
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	/
End cover	D-DC4-QU
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

ビジネスデータ

注文番号	11020000189
パッキングユニット	100
最小注文数量	100
1個あたりの重量（梱包を含めない）	13.05