
概要

製品情報



DC10-TW-11020000206

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 1000 V，Rated current: 57 A， Number of connectors: 2， Number of potentials: 1， Cross section: 0.5 mm² - 10 mm²， AWG: 20 - 6， Width: 10.2 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

製品の特長

☑Steel screw connection technology, reliable connection；
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible；
☑Unique plug-in bridge, high circuit connection efficiency；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Slotted screw
Strip length	10~12mm
Conductor cross section solid	0.5~10mm²
Conductor cross section flexible	0.5~10mm²
Conductor cross section solid AWG	20~6
screw thread	M4
Tightening torque	1.54N.m

Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	65A

IEC Electrical parameters	
Rated voltage (III / 3)	1000V
Rated current (III / 3)	57A
Rated surge voltage	8KV

Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension	
NS 35/7,5 Height	57mm
End plate width	1.5mm
NS 35/15 Height	64.5mm
length	58.7mm
width	10.2mm
Height	55.5mm

Overview	
Connection method	screw connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	/
Side marker	ZB10
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	DFA10
End cover	D-DC10-TW
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

ビジネスデータ

注文番号	11020000206
パッキングユニット	50
最小注文数量	50
1個あたりの重量（梱包を含めない）	26.1