
概要

製品情報



DCTK6-20A(H)-11020000234

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 630 V，Rated current: 41 A， Number of connectors: 2， Number of potentials: 1， Cross section: 0.5 mm² - 6 mm²， AWG: 22 - 8， Width: 8 mm，Color: gray， Mounting type: NS 35/7.5， NS 35/15

製品の特長

☑Current terminal；
☑Steel screw connection technology, reliable connection；
☑The sliding block breaks, which can realize the circuit breaking function；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

製品認証

CE

技術データ

製品チャート

3Dモデル

Wiring data

Screw type	Slotted screw
Strip length	10~11mm
Conductor cross section solid	0.5~6mm²
Conductor cross section flexible	0.5~6mm²
Conductor cross section solid AWG	22~8
screw thread	M4
Tightening torque	1.2N.m

Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

UL Electrical parameters	
Rated current	45A

IEC Electrical parameters	
Rated voltage (III / 3)	630V
Rated current (III / 3)	41A
Rated surge voltage	8KV

Environmental protection	
REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension	
NS 35/7,5 Height	46.55mm
End plate width	1.5mm
NS 35/15 Height	54.05mm
length	70.9mm
width	8mm
Height	46.1mm

Overview	
Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes
Insulation Materials	PA

Flame retardant grade, in line with UL 94	V0

アクセサリ

Marker

Top marker	/
Side marker	ZB8
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Bridge	FBRI6-RTK/S-XXP
End cover	D-DCTK6
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

ビジネスデータ

注文番号	11020000234
パッキングユニット	50
最小注文数量	50
1個あたりの重量（梱包を含めない）	20.967