概要

製品情報



PMSH-M12X-08P-MM-SL7X01-20030001059

Sensor/Actuator Cable,Cat 6A,blue,Male plug,Straight,M12,Coding X,Shielded,Trimming cable end,Cable Cable length:1m

製品の特長

☑Sealing optimization, protection level up to IP68
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

製品認証

RoHS REACH

技術データ

製品チャート

3Dモデル

Environmental conditions

Ambient temperature	-25℃...75℃
IP class	IP67

General parameters

Rated current	0.5A
	50V
Number of potentials	8
Insulation resistance	≥ 100 MΩ
Error-proof coding	X-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-109

Cable

Cable type	CAT6A S/FTP LSZH Blue
Cable type(abbreviation)	CAT6A S/FTP
Cross section	0.14mm²
AWG signal wire	26AWG
Wire structure Signal wire	7/0.16mm²
Core diameter (including insulation layer)	1.00±0.05mm
Wire color	1.White 2.Orange 3.White 4.Green 5.White 6.Brown 7.White 8.Blue knitting
Thickness, insulation	0.25mm
Cable outer diameter D	6.5 ±0.3mm

Conductor insulation material	Foam PE
	LSZH
Conductor material	Bare copper
Conductor resistance	14.8ohm/100M
Flame retardant	IEC60332-1
Halogen free	No

Dimension

Cable length	1m

アクセサリ

Accessories

Sealing cap	CAP-M12-FP-8001

ビジネスデータ

注文番号	20030001059
パッキングユニット	/
最小注文数量	100
１個あたりの重量（梱包を含めない）	/