概要

製品情報



DG212S-THR-5.0-10060001895

PCB spring terminal blocks,Rated current:17.5A.Rated voltage（III/2）:320V,pitch:5.0mm,Color:black,Contact surface :Tin

製品の特長

- ☑ PUSH-IN connection technology, fast wiring
- ☑ Suitable for THR welding process
- ☑ Universal installation method, suitable for various situations

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Reflow soldering/wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	28~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V

Rated current (B)	12A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	17.5A
Rated voltage(III/2)	320V
Rated voltage(II/2)	500V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB Soldering
Pin arrangement	Double-row in a straight line
Connection method	Quick connection
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated

Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Shell color	Black
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~130℃

アクセサリ

ビジネスデータ

注文番号	10060001895
パッキングユニット	1790
最小注文数量	
1個あたりの重量（梱包を含めない）	1.52