Przegląd

Informacje o produkcie



16A-GF-0.5-92116900014

16A silver gold female pins,Adapter wire specification0.5mm²

Zalety produktu

☑High-precision turning process, stable and reliable products;
☑Gold-plated and silver-plated are available, suitable for different environmental requirements;
☑Comprehensive products, resistant to temperature changes, shocks and harsh environments。

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Female
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984

Technical specification

Conductor cross sections（mm²）	0.5mm²
Conductor cross sections(AWG)	20AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	7.5mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe

numer zamówienia	92116900014
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	1.34