概要

製品情報



DG271V-10.0-10060002019

PCB spring terminal blocks,Rated current:76A.Rated voltage（III/2）:1000V,pitch:10.0mm,Color:green,Contact surface :Tin

製品の特長

- ☑ PUSH-IN connection technology, fast wiring
- ☑ Different poles can be combined through the side lock
- ☑ Universal installation method, suitable for various situations

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~16mm²
Conductor cross section flexible	0.2~16mm²
AWG	20~4AWG
Strip length	17mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V

Rated current (B)	70A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage(III/3)	1000V
Rated current	
	76A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Type of installation	PCB Soldering
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66

Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

アクセサリ

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

ビジネスデータ

注文番号	10060002019
パッキングユニット	525
最小注文数量	30
1個あたりの重量（梱包を含めない）	9.3