
종람

제품 장점



## 2EDGKAM-7.5-10010001883

Pluggable terminal blocks,Rated current:10A.Rated voltage （III/2）:400V,pitch:7.5mm,Color:green,Contact surface :Tin

제품 장점

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

제품 인증

기술 데이터

제품 도면

3D

Connection capacity

| | |
|---|---|
| Conductor cross section solid | 1.0~2.5mm² |
| Conductor cross section flexible | 1.0~2.5mm² |
| AWG | 28~12AWG |
| Torque | 0.4N.m |
| Strip length | 7mm |

Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A |

| | |
|---|---|
| Rated current (D) | 10A |

Electrical parameters IEC

| | |
|---|---|
| Rated voltage | 400V |
| Rated current | 10A |
| Rated voltage(III/2) | 400V |
| Rated surge voltage(III/2) | 4KV |

Item properties

| | |
|---|---|
| Connection direction | 90° |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M2.5 |
| Pitch | 7.5mm |
| Number of potentials | 4 |
| Pluggable or not | Yes |
| Number of rows | 1 |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | Copper alloy |
| Contact point metal surface | Nickel plating |
| Contact zone metal surface | Nickel plating |
| Insulation Materials | PA66 |
| Insulating material group | I |
| Flammability rating | UL94V-0 |

Mechanical tests

| | |
|---|---|
| Test Specification | IEC61984/ UL1059 |

### Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## 악세사리

### Tool

| | |
|---|---|
| Screwdriver | 0.6x3.5，Slotted screwdriver |
| Operating tool | / |

### Accessories

| | |
|---|---|
| Coding strip | 2EDG-PWI |
| Bridge | / |
| Marking strip | / |
| Others | / |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 10010001883 |
| 포장 단위 | 330 |
| MOQ | 30 |
| 제품 무게 (포장 제외) | 8.712 |