
概要

## 製品情報



# SRSH-M12A-05P-MM-SF7003-20030001370

Sensor/Actuator Female socket,M12,Coding A,Shielded,Rear panel installation/M12*1.0 Thread mounted,90° horizontal pins

## 製品の特長

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

## 製品認証

技術データ

## 製品チャート

## 3Dモデル

## Environmental conditions

| | |
|---|---|
| Ambient temperature | -40℃...105℃ |
| IP class | IP67 |

## General parameters

| | |
|---|---|
| Rated current | 60V |
| Number of potentials | 5 |
| Insulation resistance | ≥ 100 MΩ |
| Error-proof coding | A-Code |
| Overvoltage level | II |

| | |
|---|---|
| Pollution level | 3 |
| Connection method | Soldering pin |
| Insertion and pullout cycle | ≥ 100 |
| Torque | 0.4 Nm |
| Type of installation | Rear board installation |

### Material

| | |
|---|---|
| Flammability rating ,in line with UL94 | V0 |
| Contact material | CuZn |
| Material contact surface | Au |
| Contact carrier material | PA |
| Coil material | Zinc alloy, nickel plated |
| Sealing material | Silicon |

### Standards and specifications

| | |
|---|---|
| Standards/specifications | IEC 61076-2-101 |

## アクセサリ

### Accessories

| | |
|---|---|
| Sealing cap | CAP-M12-FP-8003 |

## ビジネスデータ

| | |
|---|---|
| 注文番号 | 20030001370 |
| パッキングユニット | / |
| 最小注文数量 | 100 |
| 1個あたりの重量（梱包を含めない） | / |