概要

製品情報



DG246-5.08-10060001891

Spring Type PCB Terminal Block,nominal current9A.Rated voltage(Ⅲ/2)：320V,pitch:5.08mm,Color:green,Contact surface:Tin

製品の特長

☑PUSH-IN connection technology, fast wiring
☑Universal installation method, suitable for various situations

製品認証

技術データ

製品チャート

3Dモデル

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	26~16AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A

Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	9A
Rated voltage(III/2)	320V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB Soldering
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	5.08mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0

Mechanical tests	
Test Specification	IEC60947/UL1059

Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ

Accessories	
Screwdriver	/
Operating tool	/
Marker strip	/
other	/

Tool	
Wire take tool	/
Screwdriver	/

ビジネスデータ

注文番号	10060001891
パッキングユニット	480
最小注文数量	
1個あたりの重量（梱包を含めない）	5.434