Overview

Product information



TS2.5-10070000007

Transformer terminal blocks,Rated current:24A.Rated voltage （III/2）:800V,Color:Orange ,Contact surface :Tin

Product advantages

☑ Screw connection technology,safe and reliable
☑ Rail installation method,suitable for transformer wiring

Product certification

Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.5~2.5mm²
Conductor cross section flexible	0.5~2.5mm²
AWG	24~14AWG
Torque	0.5N.m
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated current (B)	10A

Rated current (C)	10A

Electrical parameters IEC

Rated current	
	24A
Rated voltage(III/2)	800V

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	7.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

Accessories

Accessories

Coding strip	TSZB4
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10070000007
Packing unit	600
Minimum order quantity	30
Products weight (without packaging)	5.83