## Visión general

### Información del Producto



# PM-M8A-03P-FF-SR7C01-20020000216

Sensor/Actuator Cable,PVC,black,UL2517,Female plug,Angled,M8,Coding A,Unshielded,Trimming cable end,Cable Cable length:1m,UL Certification

### Ventajas del producto

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Miniature connector,Space saving
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

### Certificación del producto

## Datos técnicos

### Dibujo del producto

### Modelo 3D

### Dimension

| | |
|---|---|
| Cable length | 1m |

### Environmental conditions

| | |
|---|---|
| Ambient temperature | -25℃...80℃ |
| IP class | IP67 |

### General parameters

| | |
|---|---|
| Rated current | 3A |
| | 60V |
| Number of potentials | 3 |

| | |
|---|---|
| Insulation resistance | ≥ 100 MΩ |
| Error-proof coding | A-Code |
| Overvoltage level | II |
| Pollution level | 3 |
| Insertion and pullout cycle | ≥ 100 |
| Torque | 0.4 Nm |

Material

| | |
|---|---|
| Flammability rating ,in line with UL94 | V0 |
| Contact material | CuZn |
| Material contact surface | Au |
| Contact carrier material | PA |
| Fixture body material | TPU |
| Coil material | Copper alloy, nickel plated |
| Sealing material | Silicon |

Standards and specifications

| | |
|---|---|
| Standards/specifications | IEC 61076-2-104 |

Cable

| | |
|---|---|
| Cable type | PVC Black |
| Cable type(abbreviation) | PVC |
| UL AWM form | UL2517 |
| Cross section | 0.25mm² |
| AWG signal wire | 24AWG |
| Wire structure Signal wire | 7/0.20mm² |
| Core diameter (including insulation layer) | 1.00±0.05mm |
| Wire color | 1 Brown 3 Blue 4 Black |

| | |
|---|---|
| Thickness, insulation | 0.23mm |
| Cable outer diameter D | 4.4 ±0.2mm |
| Minimum bend radius ,fixed installation | 5*OD |
| Minimum bend radius ,mobile installation | 10*OD |
| Bending radius | 50.8mm |
| Outer sheath, material | PVC |
| Conductor insulation material | PVC |
| Conductor material | Tinned copper |
| Insulation resistance | ≥ 20 MΩ |
| Conductor resistance | Maximum 94.2Ω/km (at 20 °C) ) |
| Nominal cable voltage | 300V |
| Cable test voltage | 2000V |
| Special attributes | Silicone-free |
| Flame retardant | Compliant with UL758 |
| Halogen free | Yes |
| Other protection functions | Anti-UV |

## Accesorios

## Datos empresariales

| | |
|---|---|
| Número de pedido | 20020000216 |
| Unidad de embalaje | / |
| Cantidad mínima de pedido | 100 |
| Peso del producto (sin embalaje) | / |