Overview

Product information



FEAC-T-032A-P8-03-0.3M-01A(H)-22070000161

AC pile end charging socket, Type 2, IEC62196-2022, 32A/480V (AC), Cable: 0.3m, black with circular light strip

Product advantages

☑ Ring-shaped light strip, more distinctive
☑ Equipped with baffle structure (Broussonetia papyrifera), providing better protection
☑ Longer plugging and unplugging lifespan
☑ Different electronic lock hole positions, facilitating easier assembly

Product certification

Technical data

Product drawing

3D model

Dimension

Vehicle connector width	114mm
Cable length	5000±100mm
Strip length	100±10mm

Environmental conditions

Ambient temperature (operation)	-40℃~50℃
Maximum altitude	5000m(Above sea level)
IP class	IP55(coupling)

Electrical characteristics

Maximum charge power	24KW
Phase	3
Power pin quantity	3
Rated current of high-power contacts	32A
Power contact rated voltage	480
Signal contact rated voltage	30
Signal transmission type	Pulse width adjustment
Temperature measurement	NTC

Mechanical properties

Insertion force	< 100N
Pull out force	< 100N

Marking material

Shell color	black

Temperature Sensor

Sensor type	NTC

Environmental Product Compliance

REACH	conform
China RoHS	conform

Accessories

Appendix

/	/

Business data

Order number	22070000161

Packing unit	1
Minimum order quantity	
Products weight (without packaging)	0.5kg