종람

제품 장점



DG137T-15.0-10040007132

PCB terminal blocks，Rated current：115A，Rated voltage（III/2）：1000V，Cross section：4-35mm²，Pitch：15.0mm，Connection method：Screw connector with tension sleeve，Color：Green，Contact surface：Tin

제품 장점

☑ Fixed screw connection technology, reliable wiring
☑ Universal installation method to ensure a high degree of flexibility in device design
☑Double solder pins reduce mechanical stress on the solder joints

제품 인증

기술 데이터

제품 도면

3D

Processing notes

Process	Wave soldering/manual soldering

Connection capacity

Conductor cross section solid	1.0~2.5mm²
Conductor cross section flexible	1.0~2.5mm²
AWG	28~12AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	600V

Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	115A
Rated current (D)	5A
Rated current (C)	115A

Electrical parameters IEC

Rated voltage	1000V
Rated current	115A
Rated voltage(III/2)	1000V
Rated power frequency voltage(1min)	3.5KV

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
screw thread	M5
Pitch	15mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세사리

비즈니스 데이터

발주 번호	10040007132
포장 단위	
MOQ	
제품 무게 (포장 제외)	