종람

제품 장점



## DD-008-MC-21020000010

Heavy-duty insert,Number of contacts:8+PE,Dimension:3A,Rated voltage :400/230V,Rated current:15A,Male insert,Crimping connector

제품 장점

☑Crimping connection technology, high wiring efficiency
☑Suitable for vibration occasions；
☑The wiring harness can be pre-installed；
☑Choose contacts with different wire diameters and coatings；
☑High-density pins, saving installation space；
☑With grounding protection。

제품 인증

기술 데이터

제품 도면

3D

Marking

| | |
|---|---|
| classification | Insert |
| Series | DD |

versions

| | |
|---|---|
| Connection method | Crimping connection |
| Female/Male | Male |
| Dimension | 3A |
| Number of positions | 8 |

| | |
|---|---|
| PE Contacts | Yes |

Material characteristics

| | |
|---|---|
| Material（insert） | Polycarbonate（PC） |
| Materia（Contact） | Copper alloy |
| Surface（Contact） | Silver plated/gold plated |
| Flammability rating | V-0 |
| color | Grey/White（RAL 7032） |
| RoHS | Comply with RoHS exemptions |

Electrical parameters

| | |
|---|---|
| Rated current | 10A |
| | 250V |
| Rated pulse voltage | 4KV |
| Pollution level | 3 |
| On the basis of UL /CSARated current | 600V |
| Insulation resistance | ≥10000MΩ |
| Contact resistance | ≤3mΩ |
| Temperature range | -40℃~+125℃ |
| working life-mating cycles | ≥500 time |
| Strip length | 6-8mm |
| Conductor cross sections（mm²） | 0.14-2.5mm² |
| Conductor cross sections(AWG) | 26-14AWG |

Standards

| | |
|---|---|
| Connection meets standards | DIN EN 60664 DIN EN 61984 |

악세사리

## Accessories

| | |
|---|---|
| Crimping tool\|Removal tool | / |

## 비즈니스 데이터

| | |
|---|---|
| 발주 번호 | 21020000010 |
| 포장 단위 | 100 |
| MOQ | 5 |
| 제품 무게 (포장 제외) | 7.82 |